


SEPTEMBER, 2020

CWPVC-10

ADDITIONAL 10% CHARGE IF NOT ORDERED IN PALLET QUANTITIES.

| <b>PVC SCH 40</b><br><br><b>RIGID</b><br><br><b>ELECTRICAL CONDUIT</b><br><br> | SIZE  | O.D.  | I.D.  | MIN.<br>WALL | WEIGHT<br>PER<br>100' | FEET<br>PER<br>PALLET | BELL<br>END<br>LGTH. | PART<br>NO. |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------|-------|--------------|-----------------------|-----------------------|----------------------|-------------|
|                                                                                                                                                                  | 1/2"  | .840  | .622  | .109         | 16.12                 | 3000                  | 10'                  | 58015       |
|                                                                                                                                                                  | 3/4   | 1.050 | .824  | .113         | 21.50                 | 4400                  | 10'                  | 58025       |
|                                                                                                                                                                  | 1     | 1.315 | 1.049 | .133         | 31.89                 | 3600                  | 10'                  | 58035       |
|                                                                                                                                                                  |       |       |       |              |                       | 7200                  | 20'                  | 58030       |
|                                                                                                                                                                  | 1 1/4 | 1.660 | 1.380 | .140         | 43.24                 | 2000                  | 10'                  | 58045       |
|                                                                                                                                                                  |       |       |       |              |                       | 4000                  | 20'                  | 58042       |
|                                                                                                                                                                  | 1 1/2 | 1.900 | 1.610 | .145         | 51.65                 | 2250                  | 10'                  | 58055       |
|                                                                                                                                                                  |       |       |       |              |                       | 4500                  | 20'                  | 58050       |
|                                                                                                                                                                  | 2     | 2.375 | 2.067 | .154         | 69.85                 | 1400                  | 10'                  | 58065       |
|                                                                                                                                                                  |       |       |       |              |                       | 2800                  | 20'                  | 58060       |
|                                                                                                                                                                  | 2 1/2 | 2.875 | 2.469 | .203         | 110.80                | 930                   | 10'                  | 58075       |
|                                                                                                                                                                  |       |       |       |              |                       | 1860                  | 20'                  | 58070       |
|                                                                                                                                                                  | 3     | 3.500 | 3.068 | .216         | 145.13                | 880                   | 10'                  | 58085       |
|                                                                                                                                                                  |       |       |       |              |                       | 1760                  | 20'                  | 58080       |
|                                                                                                                                                                  | 4     | 4.500 | 4.026 | .237         | 206.63                | 570                   | 10'                  | 58095       |
|                                                                                                                                                                  |       |       |       |              |                       | 1140                  | 20'                  | 58090       |

PVC SCH 40 ELECTRICAL CONDUIT IS PRODUCED IN 10' & 20' LENGTHS WITH BELL END.

PVC SCH 40 ELECTRICAL CONDUIT IS GRAY IN COLOR.

PVC SCH 40 ELECTRICAL CONDUIT CONFORMS TO: UL 651 INCLUDING 90° C RATING  
NEMA TC 2  
SUNLIGHT RESISTANT

| % OF TRUCKLOAD PER PALLET |                   |                   |
|---------------------------|-------------------|-------------------|
| SIZE                      | %/TL<br>10' LGTH. | %/TL<br>20' LGTH. |
| 1/2                       | 0.9               | --                |
| 3/4                       | 2.1               | --                |
| 1                         | 1.7               | 3.4               |
| 1 1/4                     | 2.3               | 4.6               |
| 1 1/2                     | 2.5               | 5.0               |
| 2                         | 2.1               | 4.2               |
| 2 1/2                     | 2.3               | 4.6               |
| 3                         | 2.9               | 5.8               |
| 4                         | 3.0               | 6.0               |

CRESLINE - WEST, INC.

CORPORATE HEADQUARTERS: 600 CROSS POINTE BOULEVARD • EVANSVILLE, IN 47715 • TELEPHONE (812) 428-9300

PLANT: 3747 W. BUCKEYE ROAD • PHOENIX, AZ 85009 • TELEPHONE (602) 269-5161

www.cresline.com