



Never any need to install unsightly homemade burlap insulation wrap again. Rugged construction and great UV protection means you can leave **FrostGuard™ Insulated Blankets** on year round.

The inexpensive way to protect your backflow assembly from cold weather

Model	Lay Flat Dimensions H x L
FG-1	22½" x 22"
FG-2	22½" x 30"
FG-3	22½" x 40"
FG-3.3	27½" x 28"
FG-4	27½" x 46"
FG-5	42½" x 74"

FG-UN FrostGuards have two velcro slots for OS&Y gate valve stems

FG-UN-4	47" x 92"
FG-UN-6	54" x 108"
FG-UN-8	65" x 125"

Fabrication Specifications:

14 oz. vinyl fabric has the necessary fire retardant to meet NFPA-701 / ASTM E-84. It has been treated with anti-mildew and UV inhibitors. Edges reinforced with double row of machine stitching. Standard colors are Forest Green & Woodland Tan.

Insulation is ASTM C177 compliant, industrial grade, resilient, crushable, compressed fiberglass, available R-13 or R-30.

Reinforced grommets on bottom seam for installation of padlock.

Any RP relief valve discharge venting is un-impeded, even when bottom seams are padlocked together for best insulation protection

Warranty: BPDIGuardShack warrants this product for one (1) year from the date of purchase to be free of defects in material and workmanship. All claims must be made known to BPDIGuardShack in writing within 30 days of the defect becoming known to the purchaser. There are no warranties that extend beyond those described herein, either expressed or implied. BPDIGuardShack reserves the sole right, at it's own option to repair or replace any defective product, and shall exclude any damage caused by accident, misuse or abuse of the product. In no case shall BPDIGuardShack be liable for any incidental or consequential damages what-so-ever.

GUARDSHACK™

www.GuardShackEnclosures.com

800-266-5411